

CIM Ultra EV Transmission Fluid LV (Dry e-Motor)

Product description

CIM Ultra EV Transmission Fluid LV is a Low Viscosity fully synthetic, high-efficiency transmission fluid developed for drivetrains with dry e-motors. It is formulated to support long service life through strong wear control and thermal stability, while helping maintain drivetrain efficiency and performance as torque demands increase.

Applications

Suitable for use as an EV Transmission Fluid – Dry e-motor.

For specific application guidance, follow the OEM service instruction and consult CIM technical support.

Key features

- Low viscosity for efficient operation and fast circulation .
- High flash point characteristic .
- Stable under normal storage and use conditions.
- High shear stability.
- Excellent thermal and oxidative stability.

Typical Characteristics: CIM Ultra EV Transmission Fluid LV (Dry e-Motor)

Property	Test method	Typical value
Pour Point °C	ISO 3016	-47
Physical state	—	Liquid
Kinematic viscosity @ 40°C	(as reported)	18 cSt
Kinematic viscosity @ 100°C	(as reported)	4.4 to 4.6 cSt
Density @ 15°C	g/cm ³	0.849
Flash point (COC)	ASTM D92	202°C
Solubility in water	—	Not soluble

Specifications: Suitable for Use

Chery Tiggo Kunpeng e plus, Jetour X90	Aiways U5	Kia e-Niro, Soul EV, EV6
Dong Feng Lantuo, Voyah (dry motors)	Buick Velite	Maxus EUNIQ 7 Maxus eDeliver 3, eDeliver 9
GWM all models with dry motor	Enovate ME5	Mercedes Benz EQE+, EQS
Hozon Neta	Hyundai Kona Electric	Rimac Nevera (front motor)
Pininfarina Battista (front motor)	SGM Velite	Weltmeister EX5, EX6
Vinfast VF e34, VF e35, VF 8, VF 9		

Users advised against: Any use outside the stated application without technical confirmation.



Lab Certified Lubricants

PRODUCT DATA SHEET

EV Transmission Fluid

CIM Ultra EV Transmission Fluid LV (Dry e-Motor)

CIM Lubricants PTY (Ltd) - 486 Taljaard Street , Hermanstad Pretoria , South Africa P.O Box 11053 Suiderberg 0055
Technical Help Line 060 428 8103 / Customer Service 012 377 2507

Storage & Packaging

Store in a cool, dry, well-ventilated area.

Protect from direct sunlight and contamination.

www.cimlubricants.com

This data sheet and the information is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness.

Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.