



CIM ULTRA 2 Stroke

Overview

CIM ULTRA 2 Stroke oil is blended from Group II+ base oils, fortified with advance additive technology to meet the high demands of modern air cooled and water cooled two-stroke motorcycles and similar two stroke engines. With low ash content, CIM ULTRA 2 Stroke oil exhibits excellent anti-wear properties. Giving freedom from ring sticking and exhaust port blocking, CIM ULTRA 2 Stroke oil also gives freedom from plug fouling and piston crown deposits.

CIM ULTRA 2 Stroke oil is suitable for the use in:

- Chain saws
- Motor cycles
- Lawn mowers
- Generators

Recommended Mixing Ratio:

50:1 (2% oil) – Suitable for most modern air-cooled two-stroke engines (e.g., chainsaws, leaf blowers, trimmers).

- 1 litre of petrol : 20 ml of oil
- 1 gallon of petrol : 2.56 oz (75.7 ml) of oil

40:1 (2.5% oil) – Better for older or high-performance two-stroke engines needing extra lubrication.

- 1 Litre of petrol : 25 ml of oil
- 1 gallon of petrol : 3.2 oz (94.6 ml) of oil

- For modern equipment (e.g., Stihl, Husqvarna): 50:1
- For older engines or harsh conditions: 40:1

Specifications:

API TC	ISO-L-EGC
SAE J1536 GRADE II	JASO FC



PRODUCT DATA SHEET

2-Stroke Oil

Technical Data: CIM ULTRA 2 Stroke

Colour	Blue
Kinematic Viscosity @ 100°C (mm ² /s)	15
TBN (mg KOH/g)	2.6
Sulphated Ash (%)	0.11
Density @ 20°C ASTM 1298 Kg/L	0.8585
Viscosity Index ASTM D 2270	135.09
Pour Point ASTM D 97 °C	-9
Flash Point PMCC ASTM D 92 °C	70

CIM Ultra 2 Stroke Oil

CIM Lubricants PTY (Ltd) - 486 Taljaard Street , Hermanstad Pretoria ,South Africa P.O Box 11053 Suiderberg 0055

Technical Help Line 060 428 8103 / Customer Service 012 377 2507

www.cimlubricants.com

This data sheet and the information is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.