



PRODUCT DATA SHEET

Diesel Engine oil

Overview:

CIM Ultra 10W40 E CI4+/SL engine oil is blended from highly quality Group II+ Hydrocracked base oils. It is formulated to sustain engine durability where Exhaust Gas Re-circulation (EGR) is used and are intended for use with diesel fuels ranging in sulphur content up to 0.05% weight

Also applicable in hydraulic systems and compressor applications where the original equipment manufacturer specifies engine oil use.

Benefits:

- Protection against soot
- Controls wear on all critical engine parts, including piston rings, cam followers, liners, and rod bearings.

CIM Ultra SAE 10W40 E CI4+/SL meet or exceed the following performance levels:

Allison C4	API CI-4+/SL	Detroit Diesel DDC 93K215
ACEA E7-08/A3/B3/B4	MTU Type 2	MAN 3275 -1
MB 228.3/229.1	Cummins 20076/77/78	Volvo VDS 3
Caterpillar ECF-1A /ECF-2	Macko EO-N	Global DHD-1
JASO DH-1	Renault trucks RLD-2	Deutz DQC III - 10

Technical Data

Viscosity (cSt) Index	142
Viscosity (cSt) at 40°C	94
Viscosity (cSt) at 100°C	13.66
Pour Point (°C)	-35
Flash Point (°C)	220
TBN (mg KOH/g)	9.5
Ash Content (%)	1.1

CIM Ultra 10W40 E CI 4+/SL

CIM Lubricants PTY (Ltd) - 486 Taljaard Street , Hermanstad Pretoria ,South Africa P.O Box 11053 Suiderberg 0055

Technical Help Line 060 428 8103 / Customer Service 012 377 2507

www.cimlubricants.com This data sheet and the information is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

