



PRODUCT DATA SHEET

Gearbox oil

CIM ULTRA 75W80 (GL – 4)

DESCRIPTION

Synthetic manual transmission lubricant

Application

In Manual transmissions require special low temperature fluidity to reduce fuel consumption and facilitate gear shifting.

Recommendations

- ULTRA TRANSMISSION LUBRICANTS GL-4 75W80 may be used as a gear lubricant in manual transmissions and is specially recommended for Volvo manual transmissions

- Additive package approved with Volvo 97308 and 97309

Benefits

- Synthetic base fluids
- Provides excellent low temperature fluidity
- Facilitates equipment cold starting
- Improves gear shifting at low temperatures
- Exhibits excellent shear stability
- Offers fuel economy
- Reduces internal friction and reduces drive-line operating temperatures
- Protects against gear wear and extends equipment life
- Prohibits corrosion and protects against rust

Specifications

API GL-4	Volvo 97307
Volvo 97305	Volvo 97315

Properties

	Method	Units	Inspection Data
SAE Viscosity Grade			75W80
Absolute Density, 15 °C	D 1298	kg/m ³	842
Kinematic Viscosity, 40 °C	D 445	mm ² /s	61.6
Kinematic Viscosity, 100 °C	D 445	mm ² /s	10.35
Viscosity Index	D 2270	-	160
Brookfield Viscosity, -40 °C	D 2938	Pa.s	19
Flash Point	D 92	°C	205
Pour Point	D 97	°C	-48

CIM Ultra 75W80 GL-4

CIM Lubricants PTY (Ltd) - 486 Taljaard Street , Hermanstad Pretoria , South Africa P.O Box 11053 Suiderberg 0055

Technical Help Line 060 428 8103 / Customer Service 012 377 2507

www.cimlubricants.com

This data sheet and the information is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness.



Lab Certified Lubricants

PRODUCT DATA SHEET

Gearbox oil

Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.