



PRODUCT DATA SHEET

Automatic Transmission Fluid

CIM ULTRA ATF DX VI (6)

CIM ULTRA ATF DX VI, is an exceptional automatic transmission fluid, designed for General motors, and is formulated to provide twice the service life of a Dexron III (H) ATF, offering enhanced performance in both new and older transmissions.

Benefits:

- Improved Shear stability
- Friction durability
- Improved oxidation resistance
- Wear stability

Advantages:

- Viscosity retention even under high stress working conditions contributes to long transmission life.
- Improved transmission efficiency that promotes smooth shifting and performance.
- Excellent transmission cleanliness and durability by providing effective oxidation and thermal stability.
- Excellent friction performance and shift feel that provides unsurpassed durability for comfort transmission shifting.

Specifications:

DEXRON VI	POWER STEERING	MB 236.41
GMN 10060	ZF TE-ML11	GM J-60001
ALLISON C-4	ZF TE-ML14	LAST 2 x LONGER THAN DEXRON III

Technical Data:

SAE Grade	Viscosity (cSt) Index	Viscosity (cSt) at 40°C	Viscosity (cSt) at 100°C	Pour Point (In °C)	Flash Point (In °C)	Density at 15 C
ATF DX VI	151	29.8	6.9	-54	206	0.846

CIM Ultra ATF DX VI (6)

CIM Lubricants PTY (Ltd) - 486 Taljaard Street , Hermanstad Pretoria , South Africa P.O Box 11053 Suiderberg 0055

Technical Help Line 060 428 8103 / Customer Service 012 377 2507

www.cimlubricants.com

This data sheet and the information is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.