



Lab Certified Lubricants

PRODUCT DATA SHEET

Synthetic Gear oil

CIM Ultra EP 75W90 GL-5

CIM Ultra EP 75W90 GL-5 is synthetic, heavy-duty multi grade extreme pressure gear oil, using the latest additive technology. It is suitable for the lubrication of manual gearboxes and hypoid axle units, including synchromesh units fitted to automotive, commercial, agricultural and Industrial machines. CIM Ultra EP 75W90 GL-5 designates the type of service characteristics of gears, particularly hypoid, in heavy duty

applications and other automotive equipment operated under high speed/shock loaded, conditions.

Fortified with the following additives:

- Anti-oxidant
- Anti-wear
- Anti-foam
- Anti-corrosion, and
- Extreme pressure additives

CIM Ultra EP75W90 GL-5 meets or exceeds the following performance levels:

API GL-5	MAN M3343 TYPE S
DTFR 12B140 (MB 235.8)	ZF TE-ML 02B, 05B, 07A, 08, 12B, 16F, 17B, 19C, 21B
SCANIA STO 1:0	

Typical and Physical Characteristics

Viscosity (cSt) Index	Viscosity (cSt) at 40°C	Viscosity (cSt) at 100°C	Density at 15°C (kg/l)	Pour Point (Maximum)	Flash Point (Minimum)
198	92	16.7	0.858	< - 45°C	200 °C

CIM Ultra EP 75W90 GL5

CIM Lubricants PTY (Ltd) - 486 Taljaard Street , Hermanstad Pretoria ,South Africa P.O Box 11053 Suiderberg 0055

Technical Help Line 060 428 8103 / Customer Service 012 377 2507

www.cimlubricants.com

This data sheet and the information is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.