



PRODUCT DATA SHEET

Turbine oils

CIM ULTRA Turbine Oils

Overview

CIM ULTRA Turbine Oils are blended from highly refined GROUP II+ Hydro-cracked base oils. They contain a balanced additive package which are ashless and consisting of anti-wear, anti-rust, anti-oxidant and anti-foam additives to give outstanding levels of performance and wear protection. They can be used mainly for steam, gas and water turbine applications.

- Outstanding overall performance
- Extended service intervals
- Excellent oxidation resistance
- Excellent corrosion inhibitors
- Excellent anti-foaming properties

Applications

CIM Ultra Turbine Oils may be used in most turbine applications as well as certain air compressors. It promotes efficient, economical and safe operations.

OUTSTANDING FEATURES

Technical Data: CIM ULTRA Turbine Oils

ISO grade	32	46	68	100
Viscosity@40 degree c	32	46	68	100
Viscosity@100 degree c	5.0	7.0	8.0	11
Flashpoint °c	207	210	215	220

CIM ULTRA Turbine Oil Range

CIM LUBRICANTS PTY (Ltd) - 486 Taljaard Street, Hermanstad Pretoria, South Africa P.O Box 11053 Suiderberg 0055

Technical Help Line 060 428 8103 / Customer Service 012 377 2507

www.cimlubricants.com

This data sheet and the information is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.