

CIM GRAPHITE 3% GREASE

DESCRIPTION

This grease is dark grey/black in colour, smooth textured homogeneous mixtures of premium quality base oils and calcium-base soap incorporating finely dispersed lubricating graphite. It has high resistance to water washout. The graphite acts as a solid lubricant, reduces friction, prevents scuffing and seizures even when grease is displaced.

APPLICATION

This grease can be used in open gears, as overhead wire lubricant for trolley buses, pump glands, link pins, bushes and linkages and are ideally suited for plain bearings on welding machines, or where plain bearings are badly worn. In addition, this grease can also be used in rail and flange lubricating equipment. This grease is specially developed for the lubrication of pantograph copper strips and contact wires as well as for steam locomotives pins, bogie centres and synchro lift wire ropes.

TYPICAL CHARACTERISTIC

Appearance	Smooth Grey Black
Thickening Agent	Calcium
NGLI classification	2
Worked Penetration	265-295
Drop point C	90°C
Graphite	3%
Water content % (m/m)	2.5%

CIM Ultra Graphite Grease

CIM LUBRICANTS PTY (Ltd) - 486 Taljaard Street, Hermanstad Pretoria, South Africa P.O Box 11053 Suiderberg 0055

Technical Help Line 060 428 8103 / Customer Service 012 377 2507

www.cimlubricants.com

This data sheet and the information is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet