

CIM ULTRA PINS & BUSHES EP-2 Moly 3%

DESCRIPTION

CIM ULTRA PINS & BUSHES EP-2 Moly 3% is high-quality multi-purpose lithium-based grease made from a blend of solvent refined oils and incorporates multi-functional extreme pressure additives, as well as corrosion and oxidation inhibitors. The product is then fortified with Molybdenum Desulphated. It is suitable for operating temperatures between -30°C and 130°C.

APPLICATIONS

CIM ULTRA PINS & BUSHES EP-2 Moly 3% designed for use in highly loaded pins & bushes as well as for shock loading conditions in steel mills and CV joints. It is suitable for use in a full range of bearing speeds. The smooth consistency makes this grease ideal for use in centralized lubrication systems, and it can be used on ferrous and non-ferrous metals.

TYPICAL DATA: CIM ULTRA PINS & BUSHES EP-2 Moly 3%

Thickening Agent	Lithium
NLGI Classification	2
Colour	Grey Black
Work penetration at 25°C	265 – 295
Drop point °C	180
Oil viscosity at 40°C	200
Recommended temperature range	-30°C to 130°C
Water washout	5% (max)
Timken OK load, Kg, min	>20
Solid Lubricant % mm	3

CIM ULTRA PINS & BUSHES EP-2 Moly 3%

CIM Lubricants PTY (Ltd) - 486 Taljaard Street , Hermanstad Pretoria ,South Africa P.O Box 11053 Suiderberg 0055

Technical Help Line 060 428 8103 / Customer Service 012 377 2507

www.cimlubricants.com

This data sheet and the information is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.